


nida gravel[®] 129-139

gravel stabiliser



Driveways – Paths – Terraces

- ▶ Gravel stabiliser
- ▶ Inhibits root and weed growth from underneath
- ▶ 100% water permeable
- ▶ Easy to walk and ride across, resistant up to 400 T/sqm
- ▶ Sits into a passenger car
- ▶ Recyclable



without Nidagravel®



with Nidagravel®

Nidagravel®: an alternative to traditional pavings

Gravel gives the impression of space and combine the mineral and the vegetable. Ideal for paths, driveways, terraces etc.

Gravel adds a distinctive and spacious look to your property. It offers a firm and stable surface for pedestrians and any wheeled vehicle.

The honeycombed structure of Nidagravel® panels completely stabilises the gravel. The panel dimensions guarantee fast and easy laying.

Nidagravel infiltrates rainwater directly into the ground and avoids runoff, making it an optimal Sustainable Urban Drainage System (SUDS).

Walking, cycling, using wheelchair and pushing a pram across gravel will no longer pose the slightest problem. Loose earth, unattractive rutting, puddles and dangerous potholes will be a thing of the past.

Product characteristics*

- ◆ Honeycomb structure panel of 0.64, 0.96 or 1.92 sqm
- ◆ 100% permeable, SUDS compliant
- ◆ High compressive strength
- ◆ UV - and frost-resistant
- ◆ Trimmable
- ◆ Loose-lay installation system (no extra accessories required)
- ◆ Recyclable plastic material
- ◆ Geotextile thermally bonded on to the inside of the panels (45 g/sqm) in order to prevent weed growth



Products	129XS	129	139+
Intensity of traffic	●●●○ Paths, terraces, etc.		●●●○ Driveways, etc.
Size	800 x 800 mm (folded : 800 x 400mm)	1200 x 800 mm or XL : 1600 x 1200 mm (folded : 1200 x 800 mm)	
Thickness	± 30 mm		40 mm
Colours	White, black, pink, beige, grey*		
Cell size	± 56 mm	± 50 mm	
Compressive strength filled with gravel**	> 300 t/sqm		> 400 t/sqm
Tare weight	1,3 kg/sqm		2,1 kg/sqm
Honeycomb structure material	PP et UV stabilising agent		
Geotextile material	PET 45 g/sqm		
Quantity of gravel to be allowed for	≈ 60 kg/sqm		≈ 80 kg/sqm

* For laying guides and information, please refer to the general laying instructions
**Indicative resistance depend on gravel

Available accessories



Showbox
Cardboard display stand, to present Nidagravel.



Leaflet
Paper document with tips and stages in the laying of Nidagravel.